

ALUMINUM ELECTROLYTIC CAPACITORS



Bi-Polarized, For Audio Equipment





- Bi-polarized “nichicon MUSE” acoustic series.
- Suited for audio signal circuits.
- Compliant to the RoHS directive (2011/65/EU).



Specifications

Item	Performance Characteristics								
Category Temperature Range	-40 to +85°C								
Rated Voltage Range	6.3 to 50V								
Rated Capacitance Range	0.47 to 1000µF								
Capacitance Tolerance	±20% at 120Hz, 20°C								
Leakage Current	After 1 minute's application of rated voltage at 20°C, leakage current is not more than 0.03CV or 3 (µA), whichever is greater.								
Tangent of loss angle (tan δ)	Measurement frequency : 120Hz at 20°C								
	Rated voltage (V)	6.3	10	16	25	35	50		
	tan δ (MAX.)	0.24	0.20	0.16	0.16	0.14	0.12		
Stability at Low Temperature	Measurement frequency : 120Hz								
	Rated voltage (V)		6.3	10	16	25	35	50	
	Impedance ratio	Z-25°C / Z+20°C	4	3	2	2	2	2	
	ZT / Z20 (MAX.)	Z-40°C / Z+20°C	8	6	4	4	4		
Endurance	The specifications listed at right shall be met when the capacitors are restored to 20°C after the rated voltage is applied for 1000 hours at 85°C with the polarity inverted every 250 hours.						Capacitance change		Within ±20% of the initial capacitance value
							tan δ		150% or less than the initial specified value
							Leakage current		Less than or equal to the initial specified value
Shelf Life	After storing the capacitors under no load at 85°C for 1000 hours and then performing voltage treatment based on JIS C 5101-4 clause 4.1 at 20°C, they shall meet the specified values for the endurance characteristics listed above.								
Marking	Printed with black color letter on clear green sleeve.								

Radial Lead Type



	(mm)						
φD	5	6.3	8	10	12.5	16	
P	2.0	2.5	3.5	5.0	5.0	7.5	
φd	0.6	0.6	0.6	0.6	0.8	0.8	


α	(φD < 10)	1.0
	(φD ≥ 10)	1.5

• Please refer to page 20 about the end seal configuration.

Dimensions

		φD × L (mm)						
Cap.(µF)	V	6.3	10	16	25	35	50	
	Code	0J	1A	1C	1E	1V	1H	
0.47	R47						5 × 11	
1	010						5 × 11	
2.2	2R2						5 × 11	
3.3	3R3						5 × 11	
4.7	4R7						5 × 11	
10	100			5 × 11	5 × 11	5 × 11	6.3 × 11	
22	220		5 × 11	6.3 × 11	6.3 × 11	8 × 11.5	10 × 12.5	
33	330	5 × 11	6.3 × 11	6.3 × 11	8 × 11.5	10 × 12.5	10 × 16	
47	470	6.3 × 11	6.3 × 11	8 × 11.5	10 × 12.5	10 × 12.5	10 × 20	
100	101	8 × 11.5	10 × 12.5	10 × 12.5	10 × 16	10 × 20	12.5 × 25	
220	221	10 × 12.5	10 × 16	10 × 20	12.5 × 25	12.5 × 25	16 × 25	
330	331	10 × 16	10 × 20	12.5 × 20	12.5 × 25	16 × 25	16 × 31.5	
470	471	10 × 20	12.5 × 20	12.5 × 25	16 × 25	16 × 25		
1000	102	12.5 × 25	16 × 25	16 × 25	16 × 31.5			

Type numbering system (Example : 10V 47µF)



Please refer to page 20, 21, 22 about the formed or taped product spec.
Please refer to page 4 for the minimum order quantity.